

Health & Safety Data for:

GRIPSTRIP

Data Sheet No. 94	Revision: 20/12/16	Replaces: 08/12/16
Recommended uses:	Prefabricated Anti-skid overbanding tape.	
Known misuses / abuses:	Not known.	
1 Identification of the Substance / Preparation and of the Company / Undertaking		
Product:	Gripstrip	
Company:	Colas Limited	
Address:	Wallage Lane, Rowfant, Crawley, West Sussex RH10 4NF	
Telephone:	01342 711000	
Emergency Telephone:	01342 718346	
2 Hazard Identification		
The product is not classified according to Regulation (EC) No. 1272/2008 (CLP). To our knowledge, the pure product does not present any particular risk. No labelling applicable according to EC Regulation No. 1272/2008 (CLP).		
3 Composition / Information on Ingredients		
Bitumen, polymer, aggregate, fillers and additives none of which are present in concentration that might be considered as hazardous.		
4 First Aid Measures		
Inhalation	(Unlikely to pose any hazard). Remove affected person to fresh air, obtain medical attention if symptoms persist.	
Skin	Wash skin with soap and water as soon as possible. Seek medical advice if symptoms persist.	
Eyes	Irrigate eyes with copious amounts of water holding the eyelids apart. Continue to rinse for at least 15 minutes. Seek medical attention.	
Ingestion	Rinse mouth with water. Seek medical advice.	
5 Fire-Fighting Measures		
Extinguish fires using water fog, foam, dry powder or Carbon Dioxide (CO ₂). Cool down the containers exposed to heat with a water spray. Contain the extinguishing fluids by bunding. Protection during firefighting should be self-contained breathing apparatus and complete protective clothing.		
6 Accidental Release Measures		
Re-roll material for possible further use or disposal.		
7 Handling and Storage		
Handling	The product must be used by adequately trained persons in compliance with standards of good working methods applied to this operating situation. In the area of use, for work hygiene reasons, we advise against smoking, eating and drinking.	
Storage	Keep to the instructions on the label. Store at room temperature in a dry place away from heat sources and direct sunlight, as well as from all flames and sparks.	

8 Exposure Controls / Personal Protection Exposure Limit Values	
Ensure good ventilation. If ventilation is insufficient, wear suitable respiratory equipment. Wear protective gloves, safety glasses and protective clothing. Take all necessary precautions to avoid accidental discharge release of product outside, due to rupture of containers or transfer systems.	
9 Physical and Chemical Properties	
Physical State	Solid
Appearance	Black, metallic
Odour	Characteristic of bitumen
Flashpoint	>230°C (closed cup) (ISO 2719)
Auto-ignition temperature	>300°C
Flammability	Non flammable
Density	1.01 g/cm ³ (20°C)
Vapour Density	N/A
Solubility in water	Immiscible
pH	N/A
Viscosity at 15°C	Solid
10 Stability and Reactivity	
Storage temperature exceeding 30°C to avoid deformation of material	
11 Toxicological Information	
Acute Health Hazards and Advice	Not hazardous
12 Ecological Information	
Not classified as hazardous to the environment.	
13 Disposal Considerations	
Dispose as a controlled waste in accordance with local by-laws and Regulations.	
14 Transport Information	
Not classified as hazardous for conveyance.	
15 Regulatory Information	
Not classified as hazardous for supply.	
16 Other Information	
The references set out below give further information on specific aspects	
Legislation	CLP Regulations Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations Control of Substances Hazardous to Health Regulations The Reporting of Injuries, Diseases and Health Regulations Environment Protection Act
Guidance Notes	EH26 Occupational Skin Disease: Health and Safety Precautions EH40/2005 Workplace Exposure Limits