

Health & Safety Data Sheet for: RS BAGS

Data Sheet No: 148

Revision: 20/09/2016

Replaces: -

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : RS BAGS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Hydrocarbon binder used for road building and maintenance.

1.3. Details of the supplier of the safety data sheet

Registered company name : COLAS LIMITED

Address : Wallage Lane, Rowfant,
Crawley, West Sussex RH10 4NF UK

Telephone : + 44 1342711000

Fax : + 44 1342 711199

info@colas.co.uk

http://www.colas.co.uk

1.4. Emergency telephone number : + 44 1342718346

Association/Organisation :

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

Carcinogenicity, Category 1B (Carc. 1B, H350), Category 2 (Carc. 2, H351).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Category 3 carcinogen (Xn, R 40 Carc. Cat 3).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

Hazard symbols:



HEALTH HAZARD

Contains:

649-224-00-6 FUELS, DIESEL, GASOIL-UNSPECIFIED [A COMPLEX COMBINATION OF HYDROCARBONS PRODUCED BY THE DISTILLATION OF CRUDE OIL. IT CONSISTS OF HYDROCARBONS HAVING CARBON NUMBERS PREDOMINANTLY IN THE RANGE OF C9 THROUGH C20 AND BOILING IN THE RANGE OF APPROXIMATELY 163.

Risk phrase:

R 40 Limited evidence of a carcinogenic effect.

Safety phrase:

S 36/37 Wear suitable protective clothing and gloves.

S 60 This material and its container must be disposed of as hazardous waste.

2.2. Label elements**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard symbols :



GHS08

Signal Word :

DANGER

Product identifiers :

EC 269-822-7

FUELS, DIESEL, GASOIL-UNSPECIFIED [A COMPLEX COMBINATION OF HYDROCARBONS PRODUCED BY THE DISTILLATION OF CRUDE OIL. IT CONSISTS OF HYDROCARBONS HAVING CARBON NUMBERS PREDOMINANTLY IN THE RANGE OF C9 THROUGH C20 AND BOILING IN THE RANGE OF APPROXIMATELY 163.
FUEL OIL, RESIDUAL

EC 270-675-6

Additional labelling :

EUH208

Contains AMIDES, C18-UNSATD., N-[3-(DIMETHYLAMINE) PROPYL]. May produce an allergic reaction.
For professional use only.

Hazard statements :

H350

May cause cancer.

H351

Suspected of causing cancer.

H412

Harmful to aquatic life with long lasting effects

Precautionary statements - Prevention :

P201

Obtain special instructions before use.

P202

Do not handle until all safety precautions have been read and understood.

P273

Avoid release to the environment.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P308 + P313

IF exposed or concerned: Get medical advice/attention.

Precautionary statements - Storage :

P405

Store locked up.

Precautionary statements - Disposal :

P501

Dispose of contents/container to hazardous or special waste collection centre.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>.

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

Specific hazard :

- burns, splashing, inhalation, irritant dermal action

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 8052-42-4 EC: 232-490-9 REACH: 01-2119480172-44 BITUME		[1]	50 \leq x % < 100

National Sales Office, Products Division:
Loushers Lane, Wilderspool, Warrington,
Cheshire WA4 6RZ Tel: 01925 632616

Registered Office: Rowfant, Crawley,
West Sussex RH10 4NF. Registered in England: 2644726

A member of



Q06036 CBR613164 EMS67762 OHS500675



Part of the International Colas Group

Identification	(EC) 1272/2008	Note	%
INDEX 649-224-00-6 CAS: 68334-30-5 EC: 269-822-7 FUELS, DIESEL, GASOIL-UNSPECIFIED [A COMPLEX COMBINATION OF HYDROCARBONS PRODUCED BY THE DISTILLATION OF CRUDE OIL. IT CONSISTS OF HYDROCARBONS HAVING CARBON NUMBERS PREDOMINANTLY IN THE RANGE OF C9 THROUGH C20 AND BOILING IN THE RANGE OF APPROXIMATELY 163.	GHS08 Wng Carc. 2, H351	[1] [2]	1.1000 %
CAS: 68476-33-5 EC: 270-675-6 REACH: 01-2119474894-22 FUEL OIL, RESIDUAL	GHS07, GHS09, GHS08 Dgr Acute Tox. 4, H332 Carc. 1B, H350 Repr. 2, H361d STOT RE 2, H373 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1 EUH:066	[2]	0 <= x % < 1
CAS: 800-353-8 EC: 1379524-06-7 REACH: 01-2119971276-30 AMIDES, C18-UNSATD., N-[3-(DIMETHYLAMINE) PROPYL]	GHS05, GHS09, GHS07 Dgr Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 1

Information on ingredients :

- [1] Substance for which maximum workplace exposure limits are available.
[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

Other data :

- Chemical nature
Cationic aqueous emulsion of bituminous binder
The continuous phase is made of bitumen. The phase separation obtained during use or occurring unintentionally is called breaking.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures**In the event of exposure by inhalation :**

In the event of an allergic reaction, seek medical attention.
In case of exposition to important vapours, fumes or aerosols concentration, bring the person to fresh air.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
Wash immediately in copious amounts of water, keeping eyelids apart for at least 15 minutes and consult a specialist.
In case of contact with the hot product, COOL THE EYE IMMEDIATELY AND COPIOUSLY WITH COLD WATER for 10 minutes, keeping the eye open if possible. Take the person to a specialised medical centre.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.
In case of burns :
Apply immediately and copiously cold water for at least 20 minutes.
Never remove the product adhering to the skin.
Immediately transport to hospital.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
Keep the person exposed at rest. Do not force vomiting.
Seek medical attention, showing the label.

National Sales Office, Products Division:
Loushers Lane, Wilderspool, Warrington,
Cheshire WA4 6RZ Tel: 01925 632616

A member of



Registered Office: Rowfant, Crawley,
West Sussex RH10 4NF. Registered in England: 2644726

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label. Rinse out one's mouth with milk or water to relieve affected area. Do not induce vomiting to avoid any heartburn. Transport to a specialized hospital immediately for emergency care.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Bituminous emulsions are non-flammable products.

5.1. Extinguishing media

Suitable methods of extinction

Cool containers with water spray.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

- recovery : contain and collect the spilled product, sand the surfaces concerned if necessary.
- elimination : recover all wastes and dispose in compliance with current regulations.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Engineering / preventive measures

- Workers exposure :
- If the product is sprayed with a hose, it is recommended to wear protective mask and clothes.
- Wear the protective equipment given in §8 before handling the product.

Reduce the risk of accidents by arranging machinery and equipment so as to prevent the hot product from spilling or leaking.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

- never use solvent to help the process in case of blockage.
- never weld or cut if tanks or pipes are still containing gases.

In general, do not use an open flame in the proximity of hot bitumen without taking all necessary precautions.

Recommended equipment and procedures :

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations.
- Avoid exposure - obtain special instructions before use.
- Packages which have been opened must be reclosed carefully and stored in an upright position.
- Precautions :
 - avoid breathing vapours.
 - do not eat, drink and smoke when the product is moved or used.
- During product transfer :
 - always transfer the product by drawing up. Never reverse in a flexible tubing to avoid any bursting.
 - never decant with a flexible tubing through a manhole or unsuitable mouth.
 - do not use free-fall or spray methods when filling containers to prevent foaming.
 - do not fill the emulsion into any containers holding a product whose temperature exceeds 100°C.

ADVICES :

- Use only containers, pipes and joints resistant to hot bitumen and hydrocarbons.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

- Keep the container tightly closed in a dry, well-ventilated place.
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.
- Tanks and facilities must comply with applicable regulations.
- Avoid the use of any pumping devices likely to destabilise the emulsion.
 - to be avoided : storage temperatures below 5°C or above 90°C.
- NEVER heat a reservoir or tank if the heating elements are not adequately immersed (minimum 15 cm).
- If the storage time exceeds 15 days, moderately mix the emulsion.
- Do not heat the pumps or pipes using an open flame.
 - The heating elements should have a surface power below 1 W/cm2.

Packaging

- Always keep in packaging made of an identical material to the original.
- Suitable packaging materials :
 - Recommended : Steel, plastic
 - for lab, use plastic or glass containers
- Unsuitable packaging materials :
 - Avoid copper or aluminium alloys.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
8052-42-4	0.5 mg/m3	-	-	-	I

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
8052-42-4	5 mg/m3	10 mg/m3	-	-	-

- USA / NIOSH REL (National Institute for Occupational Safety and Health, Recommended exposure limits) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
8052-42-4	-	-	5 mg/m3	C-15 min mg/m3	-



8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVC (polyvinyl chloride)
- PVA (Polyvinyl alcohol)
- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state : Viscous liquid.

Important health, safety and environmental information

pH : Not stated.
Strongly acidic.

Boiling point/boiling range : Not relevant.

Flash point interval : Not relevant.

Vapour pressure (50°C) : Not relevant.

Density : = 1

Water solubility : Dilutable.

Melting point/melting range : 0 °C.

Self-ignition temperature : Not relevant.

Decomposition point/decomposition range : Not relevant.

9.2. Other information

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Aspect :

- physical state : more or less viscous liquid depending on the temperature and the grade
 - colour : black or brownish-black
 - odour : characteristics
- Physicochemical features
- ph : acid (1.5 to 3)

Specific temperatures
 - boiling : 100°C
 - solidification : < 0°C
 Explosivity : not applicable
 Density : 1000+/- 5 kg/m³ @25°C
 Solubility in water : dilutable

SECTION 10 : STABILITY AND REACTIVITY

limited stability at usual storage, handling and use temperatures

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- frost

Emulsion stability is limited. If emulsion has been stored for more than a few days, it should be circulated before use.

10.5. Incompatible materials

Products likely to destabilise the emulsion. Avoid all alkalis.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Splashes in the eyes may cause irritation and reversible damage

Presumed human carcinogen.

11.1.1. Substances

Acute toxicity :

FUEL OIL, RESIDUAL (CAS: 68476-33-5)

Oral route :

LD50 > 4320 mg/kg
 REACH Method B.1 (Acute Toxicity (Oral))
 Species : Rat (recommended by the CLP)

Dermal route :

LD50 = 2000 mg/kg
 REACH Method B.3 (Acute Toxicity (Dermal))
 Species : Rabbit (recommended by the CLP)

Inhalation route :

LC50 = 4000 mg/m³
 REACH Method B.2 (Acute Toxicity (Inhalation))
 Species : Rat (recommended by the CLP)

BITUME (CAS: 8052-42-4)

Oral route :

LD50 > 5000 mg/kg
 OECD Guideline 401 (Acute Oral Toxicity)
 Species : Rat (recommended by the CLP)

Dermal route :

LD50 > 2000 mg/kg
 OECD Guideline 402 (Acute Dermal Toxicity)
 Species : Rabbit (recommended by the CLP)

Inhalation route :

LC50 > 94.4 %@IDC_LA_INHAL_UNITS
 OECD Guideline 403 (Acute Inhalation Toxicity)
 Species : Rat (recommended by the CLP)

Carcinogenicity :

FUEL OIL, RESIDUAL (CAS: 68476-33-5)
Carcinogenicity Test :

Positive.

Presumed human carcinogen.

BITUME (CAS: 8052-42-4)
Carcinogenicity Test :

Negative.

No carcinogenic effect.

Reproductive toxicant :

BITUME (CAS: 8052-42-4)

Study on development :

OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction /
Developmental Toxicity Screening Test)

Species : Rat

Specific target organ systemic toxicity - repeated exposure :

FUEL OIL, RESIDUAL (CAS: 68476-33-5)

Duration of exposure : 28 days

Duration of exposure : 28 days

Species : Rat (recommended by CLP)

BITUME (CAS: 8052-42-4)

Duration of exposure : 28 days

Dermal route :

C = 200 mg/kg bodyweight/jour

OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Species : Rabbit (recommended by CLP)

Duration of exposure : 90 days

Inhalation route :

C = 103.9 %@IDC_STOTRE_INHAL_UNITS

Species : Rat (recommended by CLP)

11.1.2. Mixture**Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

The emulsion is a product used for construction and the binder, after breaking, has a long life span.

12.2.1. Substances

FUEL OIL, RESIDUAL (CAS: 68476-33-5)
Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available on cationic emulsions. Bioaccumulation of binder compounds is very unlikely because of insolubility and high molecular weight.

12.4. Mobility in soil

The product has no soil mobility.

Water : as the emulsion is dilutable and mobile in water, the binder could be conveyed on long distances.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

SECTION 15 : REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

- Container information:

No data available.

Usage restrictions apply to the product : See annex XVII of EC regulation No. 1907/2006.

For professional users only.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

- CMR: Carcinogenic, mutagenic or reprotoxic.
- ADR : European agreement concerning the international carriage of dangerous goods by Road.
- IMDG : International Maritime Dangerous Goods.
- IATA : International Air Transport Association.
- ICAO : International Civil Aviation Organisation
- RID : Regulations concerning the International carriage of Dangerous goods by rail.
- GHS08 : Health hazard
- PBT: Persistent, bioaccumulable and toxic.
- vPvB : Very persistent, very bioaccumulable.
- SVHC : Substances of very high concern.

- Made under licence of European Label System® MSDS software from InfoDyne - <http://www.infodyne.fr> -

National Sales Office, Products Division:
Loushers Lane, Wilderspool, Warrington,
Cheshire WA4 6RZ Tel: 01925 632616

Registered Office: Rowfant, Crawley,
West Sussex RH10 4NF. Registered in England: 2644726

