

Health & Safety Data for:
PREFORMED SURFACE DRESSING / PREFORMED STRESS ABSORBING MEMBRANE


Data Sheet No. 14	Revision: 01/12/16	Replaces: 29/07/16
<p>Recommended uses: Ready to use anti-skid surface dressing. NB: This product is normally used with CP Primer – refer to separate data sheet.</p> <p>Known misuses / abuses: Not known</p>		
1 Identification of the Substance / Preparation and of the Company / Undertaking		
Product:	Preformed Surface Dressing / Preformed Stress Absorbing Membrane	
Company:	Colas Limited	
Address:	Wallage Lane, Rowfant, Crawley, West Sussex RH10 4NF	
Telephone:	01342 711000	
Emergency Telephone:	01342 718346	
2 Hazard Identification		
Not classified as hazardous.		
3 Composition / Information on Ingredients		
Preparations manufactured from bitumen, mineral process oil, thermoplastic rubbers, woven glass fibre membrane and chippings. The adhesive binder is protected by release film.		
4 First Aid Measures		
Inhalation	(Unlikely to pose any hazard). Remove affected person to fresh air, obtain medical attention if symptoms persist.	
Skin	Wash skin with soap and water as soon as possible. Seek medical advice if symptoms persist.	
Eyes	Irrigate eyes with copious amounts of water holding the eyelids apart. Continue to rinse for at least 15 minutes. Seek medical attention.	
Ingestion	Seek medical advice.	
5 Fire-Fighting Measures		
Keep adjacent rolls cool by spraying with water. Extinguish fires using water fog, foam, dry powder, Carbon Dioxide (CO ₂), sand or earth. DO NOT USE WATER JET.		
6 Accidental Release Measures		
Re-roll material for possible further use or disposal.		
7 Handling and Storage		
Handling	Mechanical handling of palletised products reduces the hazards of manual lifting. Where manual lifting is unavoidable use correct kinetic lifting techniques.	
Storage	Rolls are vertically packed on pallets and must be stored and conveyed in this position, preferably under cover.	
8 Exposure Controls / Personal Protection Exposure Limit Values		
There are no relevant Workplace limits given in EH40/2005.		
Recommended Protective Clothing	Gloves	

9 Physical and Chemical Properties	
Physical State	Solid
Appearance	Black roll with surface aggregate
Odour	None
Acidity/Alkalinity	N/A
Boiling Point/Boiling Range	Decomposes above 250°C
Melting Point/Melting Range	Approximately 100°C
Flashpoint	>250°C
Flammability	Not flammable
Autoflammability	>400°C
Flammability Limits - upper - lower	N/A N/A
Explosive Properties	N/A
Oxidising Properties	N/A
Vapour Pressure at 40°C	N/A
Density at 15°C	Approximately 1.8 g/ml
Solubility - Water Solubility - Fat Solubility/Solvent	Insoluble Binder is soluble in most organic solvents
Partition Coefficient, N-Octanol water:	Not determined
Viscosity at 15°C	Solid
10 Stability and Reactivity	
Carbon Dioxide (CO ₂), Carbon Monoxide (CO), Nitrogen Oxides (NO ₂) and Hydrogen Sulphide (H ₂ S).	
11 Toxicological Information	
Acute Health Hazards and Advice	Not hazardous.
12 Ecological Information	
Not classified as hazardous to the environment.	
13 Disposal Considerations	
Dispose as a controlled waste in accordance with local by-laws and Regulations.	
14 Transport Information	
Not classified as hazardous for conveyance.	
15 Regulatory Information	
Not classified as hazardous for supply.	
16 Other Information	
The references set out below give further information on specific aspects	
Legislation	CLP Regulations Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations Control of Substances Hazardous to Health Regulations The Reporting of Injuries, Diseases and Health Regulations Environment Protection Act

National Sales Office, Products Division:
Loushers Lane, Wilderspool, Warrington,
Cheshire WA4 6RZ Tel: 01925 632616

Registered Office: Rowfant, Crawley,
West Sussex RH10 4NF. Registered in England: 2644726

A member of



Q06036

CBR613164

EM567762

OH5500675



Guidance Notes	EH26	Occupational Skin Disease: Health and Safety Precautions
	EH40/2005	Workplace Exposure Limits